

PRODUCT SPECIFICATION SHEET				11150210001291	11150210000944	11150210001176	
AUX Split Room Air Conditioner			Model	AUX-12QI	AUX-18QI	AUX-24QI	
Nameplate Parameter	Rated Capacity	Cooling	W	3500(800-3800)	5300(1300-5700)	7200(1800-7300)	
		Heating	W	3800(1000-4100)	5400(1300-5500)	7200(1800-7400)	
	Rated Power Consumption	Cooling	W	1180(100-1400)	1650(290-1800)	2300(300-340)	
		Heating	W	1100(300-1400)	1470(250-1800)	2300(300-340)	
	Rated Running Current	Cooling	A	5.5(0.7-7.8)	7.8(2.2-9.3)	11(1.5-13)	
		Heating	A	5.3(1.5-7.8)	6.5(2.0-8.0)	10(1.5-12)	
	Max. Input Power		W	1900	2500	3400	
	Max. Input Current		A	9.5	12	16	
	SEER Cooling		W/W	6.2	6.8	6.32	
	SCOP Heating		W/W	4	4	4.22	
	Power supply source		V/Ph/Hz	220-240V~/50Hz	220-240V~/50Hz	220-240V/50Hz	
	Refrigerant		/	R32	R32	R32	
	Refrigerant Charged		g	540	850	1300	
	Max. Discharge Pressure		Mpa	4.3	4.3	4.3	
	Max. Suction Pressure		Mpa	2.5	2.5	2.5	
	Air Flow Volume		m3/h	600	850	1310	
	Noise level indoor		dB (A)	53/43/41/37/31/23	58/49/45/41/37/26	64/50/47/43/38	
	Noise level outdoor		dB (A)	62	62	63	
	Indoor unit weight (Net)		Kg	8	11.5	13	
	Outdoor unit weight (Net)		Kg	21	27	31.5	
Indoor unit configuration	evaporator	Multi-bend		/	3	3	3
		Rows		Row	2	2	2
		tube pitch		mm	19.05	19.05	20.5
		row pitch		mm	23.2	11.6	12.7
	Fan motor		Model	Pcs	YYK18-4F	D-310-30-10A	D-310-50-10L
	Dimension indoor		Net Dimension (WidthxDepthxHeight)		mm	761×295×200	960×315×222
		Packing Dimension (WidthxDepthxHeight)		mm	825×367×277	1020×375×305	1155×397×312
Connection	Stop Valve		Liquid Valve	/	Dg4	DG4	Dg4
			Gas Valve	/	Dg8	DG10	Dg13
Outdoor unit configuration	Compressor Model		/	KSN89D28UE4A31	C-1RZ140H3DDF	KTN150D43UFZC31	
	Compressor Parameter	type		/	Rotary	Rotary	Rotary
		Brand		/	GMCC	SANYO	GMCC
	Fan motor		Model	/	D-35-10M	D-40-10L	D-60-10M
	Condenser	Rows		Row	1	2	2
		tube pitch		mm	22	19.05	20.5
		row pitch		mm	19.05	11.6	25.4
	Dimension outdoor	Net Dimension (WidthxDepthxHeight)		mm	709×530×280	785×555×300	825×655×335
Packing Dimension (WidthxDepthxHeight)		mm	825×595×345	888×367×590	985×400×695		
Container Loading 20/40/40HC			Sets	112/231/276	96/180/208	148	